

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

SECTION 1. IDENTIFICATION

Company name : Todol Products
25 Washington Ave
USA Natick, MA 01760
PO BOX 398

Telephone : 1-800-252-3818

Telefax : 508-651-0729

E-mail address : info@todol.com

Emergency telephone : 24/7 USA: 800-535-5053
24/7 Global: 352-323-3500

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Gases under pressure : Compressed gas

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2B

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

GHS label elements

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 + H320 Causes skin and eye irritation.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

: P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 Wear respiratory protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ atten-

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

tion.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Castor oil, polymer with polymethylenepolyphenylene isocyanate	67700-69-0	Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	$\geq 30 - < 50$
Tris(2-chloro-1-methylethyl) phosphate	13674-84-5	Acute Tox. 4; H302	$\geq 10 - < 20$
Aromatic prepolymer, polyether based	97851-17-7	Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT RE 2; H373	$\geq 10 - < 20$
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	$\geq 10 - < 20$
Aromatic prepolymer	916652-23-8	Acute Tox. 4; H332 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT RE 2; H373	$\geq 5 - < 10$

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

isobutane	75-28-5	Flam. Gas 1; H220	>= 1 - < 5
propane	74-98-6	Flam. Gas 1; H220	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Gastrointestinal discomfort
Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Harmful if swallowed.
Causes skin and eye irritation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray jet
Dry powder

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

	Foam Carbon dioxide (CO ₂)
Unsuitable extinguishing media	: Water High volume water jet
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Nitrogen oxides (NO _x) Hydrogen cyanide (hydrocyanic acid) Chlorine compounds Bromine compounds
Further information	: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Allow to solidify, use mechanical handling equipment. Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asth-

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the application area.

Take precautionary measures against static discharge.

Open drum carefully as content may be under pressure.

Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 122 °F. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 Store in original container.
 Keep in a well-ventilated place.
 Observe label precautions.
 Store in accordance with local regulations.

Materials to avoid : Explosives
 Poisonous gases
 Poisonous liquids
 Radioactive Substances

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	C	0.02 ppm 0.2 mg/m3	OSHA Z-1
		C	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm	ACGIH
isobutane	75-28-5	STEL	1,000 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

ed or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Chemicals under pressure
- Color : various
- Odor : ether-like
- Odor Threshold : No data available
- pH : Not applicable substance/mixture reacts with water
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	5100 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.05 g/cm ³ (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	132 g/l

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	Heat, flames and sparks.

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Remarks: Based on data from similar materials

Aromatic prepolymer, polyether based:

Acute inhalation toxicity : Acute toxicity estimate: 50 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : (Rat): 2,001 mg/kg
Method: OECD Test Guideline 402

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

Aromatic prepolymer:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Species : reconstructed human epidermis (RhE)
Exposure time : < 1 h
Method : OECD Test Guideline 439
Result : No skin irritation
Remarks : Based on data from similar materials

Aromatic prepolymer, polyether based:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439
Result : No skin irritation

Aromatic prepolymer:

Species : reconstructed human epidermis (RhE)
Exposure time : < 1 h
Method : OECD Test Guideline 439
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes eye irritation.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Species : Not tested on animals
Result : No eye irritation
Method : OECD Test Guideline 492
Remarks : Based on data from similar materials

Aromatic prepolymer, polyether based:

Species : Not tested on animals
Result : No eye irritation
Method : OECD Test Guideline 438

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Aromatic prepolymer:

Species : Not tested on animals
Result : No eye irritation
Method : OECD Test Guideline 438

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Dermal
Species : Mouse
Method : OECD Test Guideline 442B
Result : May cause sensitization by skin contact.
Remarks : Based on data from similar materials

Aromatic prepolymer, polyether based:

Species : Mouse
Method : OECD Test Guideline 429
Result : May cause sensitization by skin contact.

Aromatic prepolymer:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Dermal
Species : Mouse
Method : OECD Test Guideline 429
Result : May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative
Remarks: Based on data from similar materials

Aromatic prepolymer, polyether based:

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Aromatic prepolymer:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.
IARC Not applicable

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Toxicity to algae/aquatic plants : EC50 (algae): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Aromatic prepolymer, polyether based:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Raphidocelis subcapitata (freshwater green alga)): 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l

Aromatic prepolymer:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (algae): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Persistence and degradability

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Biodegradability : aerobic
Result: Not readily biodegradable.
Testing period: 28 d
Exposure time: 28 d
Kinetic:
28 d: 1.5 %
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Aromatic prepolymer, polyether based:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2.03 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Aromatic prepolymer:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.29 %
Testing period: 28 d
Exposure time: 28 d
Kinetic:
28 d: 1.29 %
Method: OECD Test Guideline 301C

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

propane:

20-year global warming potential: 0.072
100-year global warming potential: 0.02
500-year global warming potential: 0.006
Atmospheric lifetime: 0.036 yr
Radiative efficiency: 0 Wm²ppb
Further information: Miscellaneous compounds

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no
Remarks : Transport according to chapter 3.4 (LQ) possible

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Domestic regulation

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols
Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

Diphenylmethanediisocyanate, isomers and homologues 9016-87-9 >= 10 - < 20 %

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / C : Ceiling limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-1 / C : Ceiling

Notes to Reader

The data contained herein are furnished for information only and are believed to be reliable. However, Todol Products (hereafter Todol) does not assume responsibility for any results obtained by persons over whose methods Todol has no control. It is the user's responsibility to determine the suitability of Todol's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Todol specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Todol's products. Todol further disclaims any liability for consequential or incidental damages of any kind, including lost profits. This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Todol for additional assistance.

Revision Date 03/14/2024

EZ Flo Foam 675 ml

Revision Date 03/14/2024

Print Date 03/15/2024

10000030922
US / Z8