Revision Date 03/19/2024

Print Date 03/19/2024

SECTION 1. IDENTIFICATION

Company name	Todol Products 25 Washington Ave USA Natick, MA 01760 PO BOX 398
Telephone	: 1-800-252-3818
Telefax	: 508-651-0729
E-mail address	: info@todol.com
Emergency telephone	: 24/7 USA: 800-535-5053 24/7 Global: 352-323-3500
Recommended use of the chemical and restrictions on use	: For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols	:	Category 2
Gases under pressure	:	Compressed gas
Acute toxicity (Oral)	:	Category 4
Skin irritation	:	Category 2
Eye irritation	:	Category 2B
Respiratory sensitization	:	Category 1
Skin sensitization	:	Category 1
Carcinogenicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2

GHS label elements

Hazard pictograms	
Signal Word	: Danger
Hazard Statements	 H223 Flammable aerosol. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H315 + H320 Causes skin and eye irritation. H317 May cause an allergic skin reaction. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary Statements	 P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.
	Prevention:
	 P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dusts or mists. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P284 Wear respiratory protection.
	Response:
	 P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ at- tention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Revision Date 03/19/2024

Print Date 03/19/2024

 $\mathsf{P337}$ + $\mathsf{P313}$ If eye irritation persists: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410 + P402 Protect from suplight. Store in a well ventilated

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
Castor oil, polymer with polymeth- ylenepolyphenylene isocyanate	67700-69-0	Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	>= 30 - < 50
Tris(2-chloro-1-methylethyl) phos- phate	13674-84-5	Acute Tox. 4; H302	>= 10 - < 20
Aromatic prepolymer, polyether based	97851-17-7	Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT RE 2; H373	>= 10 - < 20
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 10 - < 20
Aromatic prepolymer	916652-23-8	Acute Tox. 4; H332 Resp. Sens. 1; H334 Skin Sens. 1; H317	>= 5 - < 10

SECTION 4. FIRST AID MEASURES

Print	Date	03/19/2024
1 11111	Date	00/10/2024

		STOT RE 2; H373	
isobutane	75-28-5	Flam. Gas 1; H220	>= 1 - < 5
propane	74-98-6	Flam. Gas 1; H220	>= 1 - < 5

Actual concentration is withheld as a trade secret

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.
If inhaled	:	Move to fresh air.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	Harmful if swallowed. Causes skin and eye irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if inhaled. irritant effects sensitizing effects Gastrointestinal discomfort Asthmatic appearance Cough Respiratory disorder Allergic reactions
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Revision	Date	03/19/2024
11011011	Daio	00/10/2024

Print Date 03/19/2024

		Dry powder Foam Carbon dioxide (CO2)
Unsuitable extinguishing me- dia	:	Water High volume water jet
Hazardous combustion prod- ucts	:	Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Chlorine compounds Bromine compounds
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages can- not be contained.
Methods and materials for : containment and cleaning up	Allow to solidify, use mechanical handling equipment. Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic dis- charges.
Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Revision Date 03/19/2024	Print Date 03/19/2024
	Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the appli- cation area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage :	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 122 °F. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Materials to avoid :	Explosives Poisonous gases Poisonous liquids Radioactive Substances

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of ex- posure)	Control parame- ters / Permissible concentration	Basis
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm	ACGIH
isobutane	75-28-5	STEL	1,000 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other

Revision Date 03/19/2024	Print Date 03/19/2024
	engineering controls to keep worker exposure below any rec- ommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.
Personal protective equipment	
Respiratory protection :	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aero- sol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing ap- paratus must be used.
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection :	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures :	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment be- fore entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Chemicals under pressure
Color	:	various
Odor	:	No data available
Odor Threshold	:	No data available
рН	:	Not applicable substance/mixture reacts with water
Melting point/range / Freezing point	:	No data available
		7 / 18

Revision	Date	03/19/2024
110101011	Duio	00/10/2024

Print Date 03/19/2024

Boiling point/boiling range	:	No data available		
Flash point	:	Not applicable		
Evaporation rate	:	No data available		
Flammability (solid, gas)	:	No data available		
Upper explosion limit / Upper flammability limit	:	No data available		
Lower explosion limit / Lower flammability limit	:	No data available		
Vapor pressure	:	5100 hpa		
Relative vapor density	:	No data available		
Density	:	ca. 1.05 g/cm3 (73 °F / 23 °C)		
Solubility(ies) Water solubility	:	No data available		
Solubility in other solvents	:	No data available		
Partition coefficient: n-oc- tanol/water	:	No data available		
Autoignition temperature	:	No data available		
Decomposition temperature	:	No data available		
Viscosity Viscosity, dynamic	:	No data available		
Viscosity, kinematic	:	Not applicable		
Explosive properties	:	No data available		
Oxidizing properties	:	No data available		
Volatile organic compounds (VOC) content	:	132 g/l		
CTION 10. STABILITY AND REACTIVITY				

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.

Revision Date 03/19/2024		Print Date 03/19/2024
Conditions to avoid	: Heat, flames and sparks.	
Incompatible materials	: No data available	
Hazardous decomposition products	: No decomposition if stored and applied as dir	ected.
SECTION 11. TOXICOLOGICAL IN	ORMATION	
Acute toxicity		
Harmful if swallowed.		
Components:		
Castor oil, polymer with polyr	nethylenepolyphenylene isocyanate:	
Acute oral toxicity	LD50 Oral (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials	S
Acute inhalation toxicity	ELC50 (Rat): 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Remarks: Based on data from similar materials	S
Aromatic prepolymer, polyeth	er based:	
Acute inhalation toxicity	 Acute toxicity estimate: 50 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method 	
Acute dermal toxicity	: (Rat): 2,001 mg/kg Method: OECD Test Guideline 402	

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity	:	LD50 Oral (Rat): > 10,000 mg/kg
Acute inhalation toxicity	:	LC50: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9,400 mg/kg
Aromatic prepolymer: Acute oral toxicity	:	LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity	 Method: OECD Test Guideline 423 Remarks: Based on data from similar materials : LC50 (Rat): 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment 	
Acute inhalation toxicity	Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment	
	Remarks: Based on data from similar materials	
Skin corrosion/irritation		
Causes skin irritation.		
Components:		
Castor oil, polymer with po	lymethylenepolyphenylene isocyanate:	
Species	: reconstructed human epidermis (RhE)	
Exposure time	: <1h	
Method	: OECD Test Guideline 439	
Result	: No skin irritation	
Remarks	: Based on data from similar materials	
Aromatic prepolymer, polye	ether based:	
Species	: reconstructed human epidermis (RhE)	
Method	: OECD Test Guideline 439	
Result	: No skin irritation	
Aromatic prepolymer:		
Species	: reconstructed human epidermis (RhE)	
Exposure time	: <1h	
Method	: OECD Test Guideline 439	
Result	: No skin irritation	
Remarks	: Based on data from similar materials	
Serious eye damage/eye irr	itation	
Causes eye irritation.		
Components:		
	lymethylenepolyphenylene isocyanate:	
Species	: Not tested on animals	
Result	: No eye irritation	
Method	: OECD Test Guideline 492	
Remarks	: Based on data from similar materials	
Aromatic prepolymer, polye	ether based:	
Species	: Not tested on animals	
Result	: No eye irritation	
Method	: OECD Test Guideline 438	

TodolProducts

Revision Date 03/19/2024

Print Date 03/19/2024

Aromatic prepolymer:

Species	:	Not tested on animals
Result	:	No eye irritation
Method	:	OECD Test Guideline 438

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Test Type :	:	Local lymph node assay (LLNA)
Routes of exposure	:	Dermal
Species	:	Mouse
Method	:	OECD Test Guideline 442B
Result	:	May cause sensitization by skin contact.
Remarks	:	Based on data from similar materials

Aromatic prepolymer, polyether based:

Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	May cause sensitization by skin contact.

Aromatic prepolymer:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Dermal
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:

Genotoxicity in vitro

: Test Type: Microbial mutagenesis assay (Ames test) Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: negative Remarks: Based on data from similar materials

Aromatic prepolymer, polyether based:

vision Date 03	8/19/2024	Print Date 03/19/202
Genotoxicit	y in vitro :	Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative
Aromatic p	repolymer:	
Genotoxicit	y in vitro :	Test Type: Microbial mutagenesis assay (Ames test) Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation as- say) Result: negative Remarks: Based on data from similar materials
Carcinogen	licity	
Suspected of IARC	of causing cancer. Not applicable	
OSHA	Not applicable	
NTP	Not applicable	
Reproducti	•	
Not classifie	d due to lack of data.	
STOT-singl	-	
May cause r	espiratory irritation.	
•	ated exposure	
		bugh prolonged or repeated exposure if inhaled. c reaction may occur when subsequently exposed to very low levels.
Aspiration	toxicity	
Not classifie	d due to lack of data.	

Ecotoxicity

Components:

Castor oil, polymer with polymethylenepolyphenylene isocyanate:				
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials		
Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l		

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
		Method: OECD Test Guideline 202 Remarks: Based on data from similar materials

sion Date 03/19/2024		Print Date 03/19/
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Aromatic prepolymer, polyet	her	based:
Toxicity to fish	:	LL50 (Danio rerio (zebra fish)): 100 mg/l Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 100 mg/l Exposure time: 48 h Test Type: Immobilization Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOELR (Raphidocelis subcapitata (freshwater green alga)): 100 mg/l Exposure time: 72 h Test Type: Growth inhibition Method: OECD Test Guideline 201
Diphenylmethanediisocyana	te, i	isomeres and homologues:
Toxicity to fish	÷	LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Aromatic prepolymer:		
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
aquatic invertebrates		Remarks: Based on data from similar materials

TodolProducts

mation

Revision Date 03/19/2024 Print Date 03/19/2024 Persistence and degradability **Components:** Castor oil, polymer with polymethylenepolyphenylene isocyanate: Biodegradability : aerobic Result: Not readily biodegradable. Testing period: 28 d Exposure time: 28 d Kinetic: 28 d: 1.5 % Method: OECD Test Guideline 301F Remarks: Based on data from similar materials Aromatic prepolymer, polyether based: Biodegradability 2 Result: Not readily biodegradable. Biodegradation: 2.03 % Exposure time: 28 d Method: OECD Test Guideline 301C Aromatic prepolymer: Biodegradability Result: Not readily biodegradable. : Biodegradation: 1.29 % Testing period: 28 d Exposure time: 28 d Kinetic: 28 d: 1.29 % Method: OECD Test Guideline 301C **Bioaccumulative potential** No data available Mobility in soil No data available Other adverse effects Product: Additional ecological infor-Do not empty into drains; dispose of this material and its con-:

tainer in a safe way.

soil, waterways, drains and sewers.

Avoid dispersal of spilled material and runoff and contact with

Revision Date 03/19/2024

Print Date 03/19/2024

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

propane:

20-year global warming potential: 0.072 100-year global warming potential: 0.02 500-year global warming potential: 0.006 Atmospheric lifetime: 0.036 yr Radiative efficiency: 0 Wm2ppb Further information: Miscellaneous compounds

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional lo- cal authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR		
UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas
Packing instruction (cargo	:	203
aircraft)		
Packing instruction (passen-	:	203
ger aircraft)		
IMDG-Code		
UN number		UN 1950
	•	
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no
·		

Print Date 03/19/2024

IPF-Foam 600 ml

Revision Date 03/19/2024	
Remarks	: Transport according to chapter 3.4 (LQ) possible
Domestic regulation	
49 CFR	

:	UN 1950
:	Aerosols
:	2.1
:	Not assigned by regulation
:	FLAMMABLE GAS
:	126
:	no
	:

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

```
TSCA list
```

: All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids) Gases under pressure Acute toxicity (any route of exposure) Respiratory or skin sensitization Carcinogenicity Specific target organ toxicity (single or repeated exposure) Skin corrosion or irritation Serious eye damage or eye irritation
SARA 313	:	The following components are subject to reporting levels es- tablished by SARA Title III, Section 313:

Povision	Date	03/19/2024	1
Revision	Date	03/19/2024	ŧ.

Print Date 03/19/2024

>= 10 - < 20 %

Diphenylme- 9016-87-9 thanediisocyanate, isomeres and homologues

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.si-kausa.com or 201-933-8800.

Revision Date 03/19/2024

Revision Date 03/19/2024

Print Date 03/19/2024

10000056797 US / Z8